

标准配置

- 带有A45 螺纹接头的ceramus®/ 带有A32 螺纹接头的ceramus®-classic主机一台
- 吸液管, 安装扳手, 质量检验报告和操作手册; ceramus®加配回液管
- 配套瓶口转换接头: ceramus® A32、A38 和S40; ceramus®-classic A28、S40 和A45

型号	规格(ml)	最小分度(ml)	精度(R%)	误差(CV%)	订货号
ceramus®	0.2-1.0	0.05	0.6	0.1	9312000
ceramus®	0.4-2.0	0.05	0.5	0.1	9322000
ceramus®	1.0-5.0	0.10	0.5	0.1	9332000
ceramus®	2.0-10.0	0.25	0.5	0.1	9342000
ceramus®	5.0-30.0	0.50	0.5	0.1	9352000
ceramus®	10.0-60.0	1.00	0.5	0.1	9362000



型号	规格(ml)	最小分度(ml)	精度(R%)	误差(CV%)	订货号
ceramus®-classic	0.2-1.0	0.05	0.5	0.2	9310000
ceramus®-classic	0.4-2.0	0.05	0.5	0.1	9320000
ceramus®-classic	1.0-5.0	0.10	0.5	0.1	9330000
ceramus®-classic	2.0-10.0	0.25	0.5	0.1	9340000
ceramus®-classic	5.0-30.0	0.50	0.5	0.1	9350000
ceramus®-classic	10.0-60.0	1.00	0.5	0.1	9360000



型号	规格(ml)	最小分度(ml)	精度(R%)	误差(CV%)	订货号
ceramus HF	2.0-10.0	0.25	0.5	0.1	9342300



棕色试剂瓶

名称	材质	规格	订货号
试剂瓶	Amber glass	500ml (A32)	9315000
试剂瓶	Amber glass	1000ml (A45)	9345000
试剂瓶	Amber glass	2500ml (A45)	9315200

